









1580/1860 Inks

V4204

Description

V4204 is a general purpose, **blue** MEK ink qualified for use in the Videojet 1580 and 1860 continuous inkjet (CIJ) printers. This ink has good contrast on light colored materials and is ideal for use in high-speed applications for a wide variety of substrates, when an alternate color is desired. The printed code's appearance is influenced by the substrate color.

Benefits

- · Good contrast on light colored substrates
- Cyan blue color when printed on white substrates
- Dark blue color appearance when printed on copper tubing
- Green color appearance when printed on yellow substrates
- Retort resistance when printed on metals
- · Resistant to acids, bases, mineral spirits, and oils
- No European Printing Ink Association (EuPIA) Exclusion List materials
- No CMR's (Carcinogens, Mutagens, Reproductive Toxins)

Applications

This ink is used for coding and marking where a blue color is preferred. Varying the code color is useful to identify and segment date sensitive inventory, aid in stock rotation, differentiate quality grades, or identify different regulatory standards.


V4204 delivers excellent adhesion to a wide variety of substrates, including: acrylonitrile butadiene styrene (ABS), aluminum, glass, polystyrene, polycarbonate, polyester, steel, and nylon.


A no MEK/Low VOC (V930) alternative cleaner is available.




















V4204

1580/1860 Inks

Specifications

Product	Product Type	Color	Solvent Type	Container Size	Shelf life
V4204	Ink	Blue	MEK	750 ml (-D), 1000 ml (-L)	12 months*
V7201	Make-up	Colorless to pale yellow	MEK	750 ml (-D), 1000 ml (-L)	24 months*
V901	Cleaner	Colorless to pale yellow	MEK	1 liter (-Q)	30 months*
V930	Cleaner	Colorless to pale yellow	Acetone/Ethanol	1 liter (-Q)	30 months*

Storage

Printer Parameters

Qualified Models	Operating Temperature	Operating Humidity	Nozzle Compatibility
1580, 1860	5 - 45°C	10 - 90%	60μm, 70μm

Certifications and Approvals

iQMarkTM: V4204 ink was responsibly designed and manufactured to maximize contrast, adhesion, and uptime while meeting safety, environmental, and regulatory requirements. Every batch is tested to ensure it meets strict quality control specifications.

Heavy Metals: V4204 ink meets the requirements of CONEG model legislation including 94/62/EC. For more information, refer to Knowledge Article 1153.**

RoHS/WEEE: V4204 ink meets the requirements of the RoHS 2 Directive 2011/65/EU and Directive (EU) 2015/863. For more information, refer to Knowledge Article 1159.**

REACH: V4204 ink is in compliance with EU Regulation (EC) No. 1907/2006 as amended. For more information, refer to Knowledge Article 1156.**

Halogens: V4204 ink meets the International Electrotechnical Commission (IEC) definition of Halogen-Free. For more information, refer to Knowledge Article 7920.**

Food Packaging: V4204 ink may be used on the non-food contact side of food packaging. The packaging must provide a barrier between the ink and the food. When used in this manner, the inks are in compliance per 21 CFR 170.3(e)(1), Regulation (EC) No. 10/2011, and Regulation (EC) No. 2023/2006. For more information, refer to Knowledge Article 7921.**

Other: V4204 ink does not contain major allergens, animal based raw materials, nor organisms, genetically modified or not. For more information refer to Knowledge Articles 1148, 1190, and 1152.**

**Environmental, Health, Safety, and Regulatory information can change without notice, consult the current Safety Data Sheet (SDS) which is available on the Videojet website. Knowledge Articles are available by calling or emailing Videojet.

Order supplies shop.videojet.com
Call 800-843-3610
Email info@videojet.com
Or visit www.videojet.com

©2018 Videojet Technologies Inc. - All rights reserved. Videojet Technologies Inc.'s policy is one of continued product improvement. We reserve the right to alter design and/or specifications without notice.

Videojet Technologies Inc. 1500 Mittel Blvd. Wood Dale IL 60191 / USA



^{*}Store between 2°C and 35°C.