Continuous Inkjet Inks



Description

V4264 is a black MPK/Ethanol solvent ink with lower make-up consumption than typical MEK-based inks such as Videojet V4211. Similar to V4211 and V4263, V4264 was designed for adhesion to flexible plastic film. This patent pending ink was specifically formulated to meet the strict Japan ISHL Class 2 Organic Solvent List. V4264 is ideal for use in high-speed applications for a wide variety of substrates such as plastics, metals, and glass, and is qualified for use in Videojet continuous inkjet (CIJ) printers.


Benefits


- iQMark[™] Safer and more sustainable
 - No MEK, no acetone, no methanol
 - Not CMR (Carcinogen, Mutagen, Reproductive Toxin)
 - Japan ISHL compliant
 - Swiss Food Packaging Ordinance compliant
 - Up to 50% less make-up consumption than V4211
 - Less plastic and cardboard waste
 - Lower VOC emissions and fewer printer touches
 - Excellent adhesion to flexible films, including BOPP, and rigid plastic packaging
- Resistant to acids, bases, mineral spirits, and oils
- · Performance similar to V4211 Videojet plastic ink
- · Chase conversion compatible with V4263 Videojet plastic ink, no flush required

Applications

V4264 ink is ideal for printing on flexible plastic packaging where alternatives to MEK are preferred. It delivers excellent adhesion to a wide variety of substrates including acrylonitrile butadiene styrene (ABS), aluminum, biaxial oriented polypropylene (BOPP), polystyrene, polycarbonate, and steel.

No-MEK, Low VOC (V930) and drug precursor free (V940) alternative cleaners are available.













V4264

Continuous Inkjet Inks

Specifications

Product	Product Type	Color	Solvent Type	Container Size	Shelf life
V4264	Ink	Black	MPK/Ethanol	750 ml (-D) 1000 ml (-L)	18 months*
V7250	Make-up	Colorless to pale yellow	MPK/Ethanol	750 ml (-D) 1000 ml (-L)	24 months*
V916	Cleaner	Colorless to pale yellow	MIPK	1 liter (-Q)	30 months*
V930	Cleaner	Colorless to pale yellow	Acetone/Ethanol	1 liter (-Q)	30 months*
V940	Cleaner	Colorless to pale yellow	Ethyl Acetate	1 liter (-Q)	30 months*

Storage *Store between 2°C and 35°C.

Printer Parameters

Qualified Models	Operating Temperature	Operating Humidity	Nozzle Compatibility
1240, 1280 s/w 1.001.42000 or later, 1580, 1860, 1880	5 - 45ºC	10 - 90%	60µm, 70µm

Certifications and Approvals

iQMark[™]: V4264 ink was responsibly designed and manufactured to maximize contrast, adhesion, and uptime while meeting safety, environmental, and regulatory requirements. Every batch is tested to ensure it meets strict quality control specifications. V4264 ink does not contain MEK, methanol, acetone, phthalates, polycyclic aromatic hydrocarbons, mineral oil, organotin compounds, halogenated hydrocarbons, photoinitiations, bisphenol A (BPA), major allergens, animal based raw materials, nor organisms, genetically modified or not. For information, refer to Knowledge Articles 15065, 14647, and 14634.**

Product Packaging: V4264 ink, make-up, and cleaners are shipped in sustainably forested cardboard boxes. Ink and make-up cartridge components and cleaner bottles are recyclable. For information, refer to Knowledge Article 14286.**

Food Packaging: V4264 ink may be used on the non-food contact side of food packaging. The packaging must provide a barrier between the ink and the food. When used in this manner, the ink is in compliance per 21 CFR 170.3(e)(1), Regulation (EC) No. 10/2011, and Regulation (EC) No. 2023/2006. All components in this ink are listed in Annex 10 of the Swiss Food Contact Materials Ordinance Regulation No. 817.023.21. For information, refer to Knowledge Articles 14389 and 17977.**

Heavy Metals: V4264 ink meets the requirements of CONEG model legislation including 94/62/EC. For information, refer to Knowledge Article 14629.**

RoHS: V4264 ink meets the requirements of the RoHS 2 Directive 2011/65/EU and Directive (EU) 2015/863. For information, refer to Knowledge Article 14656.**

REACH: V4264 ink is in compliance with EU Regulation (EC) No. 1907/2006 as amended. For information, refer to Knowledge Article 14655.**

Halogens: V4264 ink meets the International Electrotechnical Commission (IEC) definition of Halogen-Free. For information, refer to Knowledge Article 14375.**

Japan: V4264 ink meets both the Japan Printing Ink Manufacturing Association guidelines and Japan ISHL Class 2 Organic Solvent List. For information, refer to Knowledge Article 17886.**

**Environmental, Health, Safety, and Regulatory information can change without notice, consult the current Safety Data Sheet (SDS) which is available on the Videojet website. Knowledge Articles are available by calling or emailing Videojet.

Order supplies **shop.videojet.com** Call **800-843-3610** Email **info@videojet.com** Or visit **www.videojet.com**

Videojet Technologies Inc. 1500 Mittel Blvd. Wood Dale IL 60191 / USA



©2022 Videojet Technologies Inc. - All rights reserved. Videojet Technologies Inc.'s policy is one of continued product improvement. We reserve the right to alter design and/or specifications without notice.

