



1000 Line Inks

# V448

## Description

V448 is a lower temperature, heat-curable black MEK ink qualified for use the 1000 Line continuous inkjet (CIJ) printers. This high-performance ink has been specifically designed for coding and marking applications in the aerospace, automotive and electronics markets. It has excellent abrasion and solvent resistance when heat cured, meeting Mil-Spec 883 and Mil-Spec 202G, Method 215K durability requirements.


## Benefits

- Heat curing at 110° C (230° F) for 2 hours or 150° C (302° F) for 30 minutes achieves superior durability, including:
  - Passes Mil-Spec 883 Method 2015.14 and Mil-Spec 202, Method 215 solvents
  - Resistance to other common solvents, including: acetone, MEK, transmission fluid, gasoline, diesel fuel, ethanol, and isopropanol (IPA)
  - Rub, scratch, tape, and transfer resistance
- Passes NASA's outgassing specification when cured at 175° C (347° F) for 2 hours
- Resistant to acids, bases, terpene defluxer, mineral spirits, oils, and retort processing

## Applications

V448 ink is used for coding and marking metal and ceramic parts, including gold, nickel, and titanium, which go through a heat curing process after printing and require a permanent code. It is also used for coding cans that require retort and transfer resistance. This ink delivers excellent adhesion to polystyrene, steel, and nylon.

Low VOC (V930) cleaner, compliant with the California SCAQMD Rule 1171, is available.



### Adhesion




### Light Resistance



### Dry Time (seconds)



### Dry Heat Resistance (maximum)



### Chemical Resistance



# V448

## 1000 Line Inks

### Specifications

Product	Product Type	Color	Solvent Type	Container Size	Shelf life
V448	Ink	Black	MEK	750 ml (-D)	12 months*
V748	Make-up	Colorless to pale yellow	MEK	750 ml (-D)	24 months*
V901	Cleaner	Colorless to pale yellow	MEK	1 liter (-Q)	30 months*
V930	Cleaner	Colorless to pale yellow	Acetone/Ethanol	1 liter (-Q)	30 months*

**Storage** \*Store between 2°C and 35°C.

### Printer Parameters

Qualified Models	Operating Temperature	Operating Humidity	Nozzle Compatibility
12X0, 15X0, 16X0, 1610DH	5-45°C	10-90%	60µm, 70µm

### Certifications and Approvals –

**iQMark™:** V448 ink was responsibly designed and manufactured to maximize contrast, adhesion, and uptime while meeting safety, environmental, and regulatory requirements. Every batch is tested to ensure it meets strict quality control specifications.

**Heavy Metals:** V448 ink meets the requirements of CONEG model legislation including 94/62/EC. For more information, refer to Knowledge Article 1153.\*\*

**RoHS/WEEE:** V448 ink meets the requirements of the RoHS 2 Directive 2011/65/EU and Directive (EU) 2015/863. For more information, refer to Knowledge Article 1159.\*\*

**REACH:** V448 ink is in compliance with EU Regulation (EC) No. 1907/2006 as amended. For more information, refer to Knowledge Article 1156.\*\*

**Halogens:** V448 ink meets the International Electrotechnical Commission (IEC) definition of Halogen-Free. For more information, refer to Knowledge Article 7920.\*\*

**Food Packaging:** V448 ink may be used on the non-food contact side of food packaging. The packaging must provide a barrier between the ink and the food. When used in this manner, the inks are in compliance per 21 CFR 170.3(e)(1), Regulation (EC) No. 10/2011, and Regulation (EC) No. 2023/2006. For more information, refer to Knowledge Article 7921.\*\*

**Other:** V448 ink does not contain carcinogens, mutagens, reproductive toxins, major allergens, animal based raw materials, nor organisms, genetically modified or not. For more information refer to Knowledge Articles 1148, 1190, and 1152.\*\*

\*\*Environmental, Health, Safety, and Regulatory information can change without notice, consult the current Safety Data Sheet (SDS) which is available on the Videojet website. Knowledge Articles are available by calling or emailing Videojet.

Order Supplies [shop.videojet.com](http://shop.videojet.com)

Call **800-843-3610**

Email [info@videojet.com](mailto:info@videojet.com)

Or visit [www.videojet.com](http://www.videojet.com)

Videojet Technologies Inc.

1500 Mittel Blvd. Wood Dale IL 60191 / USA

©2019 Videojet Technologies Inc. - All rights reserved.  
Videojet Technologies Inc.'s policy is one of continued  
product improvement. We reserve the right to alter  
design and/or specifications without notice.

