









Thermal Transfer Overprinting

# Videojet 6230

The Videojet 6230 delivers easy usability with built-in Code Assurance to help significantly reduce costly coding errors when marking onto flexible packaging.

Achieve increased reliability and improved code quality with the Videojet 6230 Thermal Transfer Overprinter (TTO). An airless printer for the most versatile production line installation, the 6230 features built-in code assurance and simple usability to help reduce flexible packaging coding error.

Code assurance comes as standard in the Videojet 6230 printer when using templates created by CLARISOFT™ or VideojetConnect™ Design software. These simple code creation tools help reduce operator interactions resulting in fewer user errors and unnecessary waste and rework.



#### Simple usability

- Simple change ribbon cassette, with pushbutton lock mechanism, allows for fast and easy ribbon replacement
- Intuitive tablet-like 5" touchscreen controller with CLARiTY™ interface used in other Videojet technologies

## **Built-in productivity**

- Precise ribbon control with bidirectional stepper motors minimizes gaps between codes and reduces ribbon wastage
- 700m ribbon length requires fewer ribbon changes versus hot stamp or other competitive TTO systems
- Simple ribbon path that ensures fast changeovers and a more efficient operation

#### Fits your unique production needs

- Airless operation removes the need for plant air
- Offers high-quality codes up to speeds of 150 packs / minute
- Single design printhead for intermittent or continuous printing
- Compact design easily integrates into most production lines

## Code Assurance

- WYSIWYG print preview allows operators to confirm the correct code is selected
- Built-in Code Assurance software helps to reduce operator-induced errors, decreasing unnecessary product waste and rework
- Real-time clock stamp avoids date errors
- Benefit from simple code creation with VideojetConnect Design or CLARiSOFT software

## Videojet® 6230

## Thermal Transfer Overprinting

#### Printhead

32mm, 200 dpi (8 dots/mm)

#### Print Area

Continuous mode: Max. 32mm x 100mm (1.26" x 3.93") Intermittent mode: Max. 32mm x 47mm (1.26" x 1.85")

#### **Printing Modes**

Continuous & Intermittent modes in the same machine

#### **Print Speed**

Intermittent: 50mm/sec. to 300mm/sec. (2.0"/sec to 11.8"/sec) Continuous: 40mm/sec. to 500mm/sec. (1.6"/sec to 19.7"/sec)

#### Operator Interface

5.0" Color QVGA CSTN LCD and touch screen (800 x 480 pixels) WYSIWYG print preview On-board diagnostics 3 levels of password protection Multiple language support

#### **Ribbon Drive**

Solid-state, clutchless bi-directional ribbon drive, including

- Ribbon break detection
- End of reel detection
- Ribbon consumption indication
- Ribbon Saving Mode: Radial

#### **Printing Capabilities**

Full downloadable font support using Windows® TrueType® fonts Fixed and variable text and numeric data User entered text and numeric data (including Chinese) Flexible date / time formats (based on internal real time clock) Auto best before date calculations Flexible shift code formats

#### **Bar Codes**

EAN8, EAN13, UPCA, UPCE and QR codes

#### Ribbon Length

700 meters (766 yds.) maximum, available in variety of grades and colors

#### **Ribbon Widths**

0.8" (20mm) min, 1.3" (33mm) max

#### Image Management

Videojet CLARiSOFT™ CLARiSUITE™ or VideojetConnect™ Design Template Management software

Storage

Internal memory 30 MB, expandable to 4GB

Message upload USB memory stick

Ethernet

RS232

#### Network Management Software

CLARINET™

#### Remote Coder Configuration Software

CLARiTY™ Configuration Manager (included)

#### **External Communications**

USB memory stick, ethernet, RS232, ASCII and binary communications

#### **External Inputs**

Print Go

Inhibit Print

Encoder (single phase or quadrature)

#### **External Outputs**

Warning

Busy

Printing

#### Standard installation options leader/follower configuration

Up to four Videojet 6230 printers controlled via a single CLARiTY™ control unit


#### **Power Supply**

100-240 VAC, 50/60Hz, 24V (120W) 5A


#### **Operating Temperature**

32°-104°F (0°-40° C)

#### Printer body



#### Control panel











### **New printer quote 866-871-3226**

Order supplies shop.videojet.com Call **800-843-3610** Email info@videojet.com or visit www.videojet.com

Videojet Technologies Inc. 1500 Mittel Blvd. Wood Dale IL 60191 / USA ©2024 Videojet Technologies Inc. — All rights reserved.

Videojet Technologies Inc.'s policy is one of continued product improvement. We reserve the right to alter design and/or specifications without notice. Windows is a registered trademark of Microsoft Corporation. TrueType is a registered trademark of Apple Computer, Inc.

Part No. SI 000662 ss-6230-us-0434 Printed in U.S.A.

