

Thermal Inkjet

## Videojet<sup>®</sup> 8510 Wolke m600<sup>®</sup> print sample guide













### Clear, consistent codes

The Videojet 8510 and Wolke m600 printers are the among the highest resolution industrial Inkjet printers in the market. This is accomplished through the use of HP thermal Inkjet cartridges, which have a maximum print resolution of 600 x 600 dpi. High resolution means clear, easy to read alphanumeric characters, while enabling more complex coding options and the ability to print 1-dimensional bar codes (UPC, GS1 128), alternate fonts, logos, and the increasingly popular 2-dimensional codes such as GS1 DataMatrix and Quick Response (QR) codes. The benefits do not stop there. Because the cartridge contains the printhead and ink supply, there is no costly maintenance associated with pumps, filters, or tubing. There are no messy ink changes or nozzle washdown procedures Ultimately, the simple design translates to easy operation through fast cartridge replacement. The 8510 and m600 thermal Inkjet printers meet the needs of a variety of applications.

### **Consumption Chart**

Font Height (mm)	Code Dimensions (mm)	Approx. Number of Codes Per Cartridge	Print Sample
3.0	3 x 21	538,000	9-30-2015
3.0	3 x 32	359,000	EXP 9-30-2015
3.0	7 x 20	269,000	9-30-2015 A62835T
3.0	7 x 32	186,000	EXP 9-30-2015 LOT A62835T
2.0	9 x 39	124,000	GTIN 03453120000011 EXP 09-25-15 LOT ABCD1234
2.5	12.7 x 36	56,000	2 94761 52937 9
1.8	12.7 x 70	27,000	(10)0114254(99)11:21

All samples shown above were printed at 300 x 300 dpi with Premium Black ink (part # WLK660068). Ink consumption varies based on the print resolution selected.

# Line speed vs. horizontal resolution of Videojet and Wolke printers

The maximum line speed of 8510 and m600 printers is determined only by the horizontal resolution setting of the code printed. The code height is a function of the number of printheads selected, and is independent of the production line speed. See chart below for details. Regardless of whether the code is a single line of text, multiple lines of text, tall bar codes, complex graphics, or any combination thereof, productivity will never be compromised by the amount of content required in the code.

		Vertical Resolu	tion (dpi)	Max Line Speed (feet/min.)	Max Print Heigl	nt (inches/mm)
		600	300		8510, m600 touch, m600 advanced	m600 basic
	600	LOT A62835T	LOT A62835T	100	2 inches (50.8mm)	•
	450	LOT A62835T	LOT A62835T	130		1 inch (25.4mm)
lpi)	360	LOT A62835T	LOT A62835T	160		
Horizontal Resolution (dpi)	300	LOT A62835T	LOT A62835T	200		
Horizon	240	LOT A62835T	LOT A62835T	250		
	200	LOT A62835T	LOT A62835T	300		
-	180	LOT A62835T	LOT A62835T	330		
	150	LOT A 62835T	LOT A62835T	400		

All samples shown above were printed with Premium Black ink (part # WLK660068). 300 x 300 dpi represents the industry standard for coding primary packaging. Typical dry times are 1-2 seconds. While print resolutions below 300 x 300 dpi may improve the dry time, increasing the print resolution may result in longer dry times. Please contact your Videojet representative for a complimentary evaluation.

#### Capabilities to meet just about any specification — including bar codes, fonts, graphics and more.

Description	Print Sample				
Linear bar codes Wide range of bar codes for automatic identification. UPC A&E EAN 8 & 13; Code 128 A, B&C UCC/EAN 128; Code 39; Interleaved 2 of 5. (Samples shown were printed at 300 x 300 dpi using Premium Black ink)	1234 5670 EAN 8 1234567890 Code 39	1 234567 890128 EAN 13 1 23456 78901 2 1 23456 78901 2 UPC-A	1234567890 EAN 128 1234567890 1234567890 Codabar		
2D codes Wide range of standard 2D and rectangular 2D DataMatrix, including GS1 (Samples shown were printed at 300 x 300 dpi using Premium Black ink)		DataMatrix	QR Code		
Note: Not all 2D codes available on all printers	(01)12345678901237 (17)110718 GS1 Databar - Stacked	(01)12345678901237 (17)110718 GS1 Databar - Limited	MicroPDF 417		
Logos and graphics		FRAGILE			
Font sizes User-defined font sizes are fully adjustable. All TrueType <sup>®</sup> fonts available on 8510 / m600 touch.	<sup>2mm Arial</sup> 3mm Arial 5mm Arial <b>12mm</b>				
Specialty fonts For use with Optical Character Recognition	Videojet Technolo OCR-A	gies Videoje	t Technologies OCR-В		

### Call us free on **0800 500 3023** Email **uksales@videojet.com** or visit **www.videojet.co.uk**

Videojet Technologies Ltd. 4 & 5 Ermine Centre, Lancaster Way, Huntingdon, Cambridgeshire PE29 6XX / UK  $\ensuremath{\mathbb C}$  2017 Videojet Technologies Inc. — All rights reserved.

Videojet Technologies Inc.'s policy is one of continued product improvement. We reserve the right to alter design and/or specifications without notice. TrueType is a registered trademark of Apple Computer, Inc.

Part No. SL000530 pg-8510-wolke-m600-models-en-0217

