



Large Character Inkjet

# Videojet® 2120

The Videojet 2120 is an easy-to-use printer for applying one or two lines of alphanumeric codes to a variety of products or packages.

With a choice of printheads and inks, the 2120 is able to print on a wide range of porous and non-porous materials. It can control two printheads for opposite side case coding, and also offers multiple printer control from one screen for more complex, multi-line coding. Compact printhead design provides easy integration into existing conveyance systems and printhead slant control technology allows the printhead to be mounted at an angle so the text message style, density and height can be matched to the case design.



## Uptime Advantage

- Supports one 16-valve or two 7-valve printheads to produce a variety of character heights and multi-line codes
- Leader/follower functionality allows up to four printers to be controlled from one controller for more efficient job management

## Built-in productivity

- On-screen editor allows you to create and edit messages on the fly
- On-screen indicators report ink use, job status, message preview, counts and other production details at a central location for controlling and interacting with the printer

## Code Assurance

- Single point message selection is delivered to multiple devices
- Can be connected to all Ethernet devices, including scales and scanners, throughout the production floor
- Control and access can be limited with passwords to help ensure your production continues unimpeded

## Simple usability

- Built-in configuration wizard shortens system setup time by guiding the operator through the installation process
- Printer can operate in standalone mode using intuitive interface or be networked to PLCs or factory management systems for centralized control

# Videojet® 2120

## Large Character Inkjet

### System Includes

User interface and controller  
External power supply and bracket  
Printhead(s)  
Printhead cable(s)  
Ink system plus level detect, 1 Liter  
Level detect harness  
Bracket kit  
Product sensor

### Built-in Software Functions

Time of day, internal or remote  
Real Time Clock (RTC)  
Counters: increment and decrement numbers or characters  
Remote download through RS232 or TCP/IP communication  
Print delay  
Print orientation: inverted, reversed or both

### Print Formats

Upper and lower case characters  
Multi-stroke characters  
Bold characters  
Adjustable character widths  
Print orientation: inverted, reversed or both

### Print Height and Print Speeds

Note: Minimum speed is 26 fpm (8 m/min.) for both 700 and 800 series printheads

Note: Dot size setting can have an effect on the maximum line speed

### 700 Series printheads (for porous substrates)

Printhead	# of dots	Print Height	Max Line Speed
707	7	0.5" 13 mm	236 fpm 72 m/min.
707	7	0.8" 20 mm	371 fpm 113 m/min.
716	16	1.2" 30 mm	236 fpm 72 m/min.
716	16	2.0" 50 mm	371 fpm 113 m/min.

### 800 Series printheads (for nonporous substrates)

Printhead	# of dots	Print Height		Max Line Speed	
		55°	80°	55°	80°
807	7	1.5" 37 mm	0.4" 11 mm	413 fpm 126 m/min.	285 fpm 87 m/min.
816*	16	3.6" 92 mm	1.1" 28 mm	413 fpm 126 m/min.	285 fpm 87 m/min.

\*For 5x5 font matrix, max speed at stated print height is 220 fpm (67 m/min.)

### Inks and Delivery Systems

Colours: black, red, blue  
Capacity: Standard 1 liter; 5 gallon with optional ADS Plus  
Characters/liter

707 Printhead (7 Dot Font) - 300,000 characters/liter

716 Printhead (16 Dot Font) - 56,000 characters/liter

807 Printhead (7 Dot Font) - 400,000 characters/liter

816 Printhead (16 Dot Font) - 60,000 characters/liter

Surfaces: porous and non-porous

Delivery: optional Air Delivery System (ADS Plus)

### Electrical Specifications

Mains Voltage: 100 to 240 VAC

Frequency: 47 to 63 Hz

Input Current: 1.07 A Max

Safety Protection: Class I

### Environmental Specifications

Operating temperature: 5°C to 40°C (41°F to 104°F)

Rate of change of ambient temperature: 10°C (50°F) per hour maximum

Relative humidity: 10 to 90% non-condensing

### Weight

CLARITY Controller 2.54 lbs (1.15 Kg)

700 Series printhead (7 valve) 1.10 lbs (0.5 Kg)

700 Series printhead (16 valve) 1.99 lbs (0.9 Kg)


800 Series printhead (7 valve) 0.88 lbs (0.4 Kg)

800 Series printhead (16 valve) 1.87 lbs (0.85 Kg)


CERTIFIED  
ISO 9001  
DOCUMENTED QUALITY




### Controller Dimensions



### 700 Series Printhead Dimensions



### 800 Series Printhead Dimensions



Call us free on **0800 500 3023**

Email **uksales@videojet.com**

or visit **www.videojet.co.uk**

Videojet Technologies Ltd.

4 & 5 Ermine Centre, Huntingdon, Cambridgeshire PE29 6XX / UK

Call us free on **+353 1 450 2833**

Email **irelandsales@videojet.com**

or visit **www.videojet.ie**

Videojet Ireland

C2, South City Business Park, Tallaght, Dublin 24 / Ireland

© 2022 Videojet Technologies Inc. — All rights reserved.

Videojet Technologies Inc.'s policy is one of continued product improvement.  
We reserve the right to alter design and/or specifications without notice.

Part No. SL000500  
ss-2120-en-0922