

Laser Marking System

Videojet® 3640

Exceed current marking speed expectations on the production line with the Videojet 3640 laser marking system, engineered to process complex codes at highest speeds, with the industry's widest mark field.

Meet permanent coding needs today and in the future, with the high-speed capabilities of the Videojet 3640 CO₂ laser marking solution.

With print speeds of up to 2,100 characters per second and 150,000 products per hour, the 3640 is an ideal solution to help address highest speed and volume applications in the pharmaceutical, tobacco and beverage industries.



Uptime Advantage

- Optimised for high-speed and high-volume production lines
- Maximise printer availability with long-life, air-cooled laser sources
- Optional VideojetConnect™ Remote Service allows access to Videojet experts to help improve productivity and troubleshoot potential issues

Industrial Design

- Suitable for harsh environments where dust and humidity are a challenge and where the system is regularly washed down
- Available with an ingress protection level of IP65
- Designed for 24/7 operation in beverage, food, pharmaceutical and tobacco lines

Code Assurance

- Optional CLARiTY™ Laser Controller offers built-in software features that help reduce operator errors and ensure products are coded correctly
- High-quality, permanent codes help assure product traceability and tamper-proofing
- High-resolution marking head delivers consistent, crisp codes

Simple integration

- Compact, high-power laser marking system in the industry
- Easily integrate the laser marking system, even into production lines that have space limitations
- Widest marking field reduces the number of lasers that are required to cover multi-lane / wide web applications, reducing investment and running cost

Videojet® 3640

Laser Marking System

Marking speed

Up to 2,100 characters/sec.⁽¹⁾

Line speed

Up to 15m/sec. (49ft/sec.)⁽¹⁾

Marking window

Approx. 30.8 x 38.2mm² to 601.0 x 439.8mm²

Wavelengths

10.6µm, 10.2µm and 9.3µm

Marking formats

Standard industrial fonts (Type 1 Windows® TrueType®) and Single line fonts
Machine readable codes (OCR, 2D-matrix, etc.)
Bar codes: BC25, BC25i, BC39, BC128, GS1-128, EAN13, UPC_A, RSS14, RSS14 Truncated, RSS14 Stacked, RSS14 Stacked Omnidirectional, RSS Limited, RSS Expanded, etc.
Graphics, logos, symbols, etc.
Linear, circular, angular, reverse, rotate
Sequential and batch numbering
Automatic date, layer and time coding; real-time clock
Dot mode enables marking 2D codes faster than traditional grid mode

Laser tube

Sealed CO₂ laser, power class 60-Watt

Beam deflection

Steered beam with digital high-speed galvanometre scanners

Focusing

Focal lengths: 64/ 95/ 127/ 190/ 254 mm (2.5/ 3.75/ 5.0/ 7.5/ 10.0 inches);
63.5/ 85/ 100/ 150/ 200/ 300/ 351/ 400 mm (2.50/ 3.35/ 3.94/ 5.9/ 7.87/ 11.8/ 13.8/ 15.75 inches);
100/ 150/ 200/ 300/ 351 mm (3.9/ 5.9/ 7.9/ 11.8/ 13.8 inches);
400/ 500/ 600 mm (15.75/ 19.68/ 23.62 inches)

Multiple operator interface options


Handheld controller
PC software
TCS Touch Control Software
CLARiTY™ Laser Controller
Smart Graph Com

Language capabilities⁽²⁾

Arabic, Bulgarian, Czech, Danish, English, German, Greek, Finnish, French, Hebrew, Hungarian, Italian, Japanese, Korean, Dutch, Norwegian, Polish, Portuguese, Romanian, Russian, Serbian, Simplified Chinese, Slovak, Spanish, Swedish, Thai, Traditional Chinese, Turkish, Vietnamese; interface dependent. Additional languages available with Smart Graph software.

⁽¹⁾ Maximum marking and line speed is application dependent

⁽²⁾ With optional CLARiTY™ Laser Controller



Communication

Ethernet, TCP/IP and RS232 optional
Inputs for encoders and product detector triggers
16 inputs / 11 outputs for start/stop signals, machine/operator interlocks, alarm outputs; in addition to the safety circuits
Customer-specific solutions available

Integration

Direct integration into complex production lines via scripting interface
Flexible beam delivery options (beam extension unit/ beam turning unit)
Detachable umbilical for simple integration; available in 3 lengths

Electrical requirements

100-240 VAC (autorange), -50/60Hz, 1PH, 1.15kW

Cooling system

Air cooled

Environment

Temperature 40-105° F (5-40° C)
Humidity 10%-90%, non-condensing

Sealing and safety standards

Supply Unit: IP54, optional IP65
Marking Unit: IP54, optional IP65
Optional safety module provides Performance Level d (PFL-d) in accordance to EN 13849-1
IEC/EN 60825-1:2014


Approximate weight

Supply unit: IP54/IP65 25.4lbs. (11.5kg)
Marking unit: IP54 58.4 lbs. (26.5kg); IP65 59.5lbs. (27kg)


Applicable certifications

CE, TÜV/NRTL, FCC
Compliance (no certification required): ROHS, CDRH/FDA

Marking unit dimensions - IP54 with SHC60c marking head



Supply cabinet dimensions - IP54



Call us free on **0800 500 3023**
Email **uksales@videojet.com**
or visit **www.videojet.co.uk**

Videojet Technologies Ltd.
4 & 5 Ermine Centre, Huntingdon, Cambridgeshire PE29 6XX / UK

Call us free on **+353 1 450 2833**
Email **irelandsales@videojet.com**
or visit **www.videojet.ie**

Videojet Ireland
C2, South City Business Park, Tallaght, Dublin 24 / Ireland

© 2019 Videojet Technologies Inc. — All rights reserved.

Videojet Technologies Inc.'s policy is one of continued product improvement. We reserve the right to alter design and/or specifications without notice. Windows is a registered trademark of Microsoft Corporation. TrueType is a registered trademark of Apple Inc., registered in the United States and other countries.

Part No. SL000642
ss-3640-en-0819

